

XT2001M XT6602M 规格书

性能参数	图像传感器	640×480 CMOS		
	环境光照强度	0~100000 Lux		
	识读码制	2D	PDF417, Data Matrix, QR, Micro QR	
		1D	Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5(European Matrix 2 of 5), Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand	
	识读精度	≥3mil		
	典型识读景深	EAN-13	40mm-355mm (13mil)	
		Code 39	28mm-155mm (5mil)	
		PDF 417	28mm-95mm (6.67mil)	
		Data Matrix	25mm-95mm (10mil)	
		QR	25mm-150mm (15mil)	
条码灵敏度	倾斜	±60°@ 0°Roll and 0° Skew		
	旋转	360°@ 0°Pitch and 0° Skew		
	偏转	±55°@ 0°Roll and 0° Pitch		
最低对比度	30%			
数据接口	RS-232, USB			
物理参数	尺寸（长×宽×高）	5.3*3.5*0.8mm（手工测量，存在误差）		
	重量	5.7 克		
	提示方式	蜂鸣器、LED 指示灯		
	电流	最大电流	<200mA	
		工作电流	150mA±15mA	
		待机电流	80mA±2mA	
环境参数	工作温度	-20℃~50℃		
	储存温度	-40℃~70℃		
	相对湿度	5%~95%（无凝结）		